

## Drillschrauben (Tapits)


mit Sechskantkopf, Längsschlitz und Sperrverzahnung

### Drill-screws (Tapits)

with Heagon washer head and slot with locking serration under head

### Vis à tôle (Tapits)

Tête hexagonale, embase cylindrique avec crantage sous tête



1 Stahl verzinkt  
Steel zinc plated  
Acier zingué

Ø 4,2 mm

SW = 1/4"

↳ = A




4,2 x 13 mm	1/4"	1000	50101 42 130

Ø 4,8 mm

SW = 8 mm

↳ = A

4,8 x 19 mm	8 mm	500	50101 48 190



1 A2 W.-Nr. 1.4301/03 AISI 305  
A2 W.-Nr. 1.4301/03 AISI 305  
A2 W.-Nr. 1.4301/03 AISI 305

Ø 4,2 mm

SW = 7 mm

↳ = A




4,2 x 13 mm	7 mm	1000	50301 42 130

Ø 4,8 mm

SW = 8 mm

↳ = A

4,8 x 16 mm	8 mm	500	50301 48 160



1 C1 W.-Nr. 1.4006 AISI 410 [GOEBEL silber GL](#)  
C1 W.-Nr. 1.4006 AISI 410 [GOEBEL silver GL](#)  
C1 W.-Nr. 1.4006 AISI 410 [GOEBEL GL argenté](#)

Ø 4,2 mm

SW = 1/4"

↳ = A

4,2 x 13 mm	1/4"	1000	50631 42 130